

DH-HCVR0804AH-VD-I

8 Channel Tribrid Intelligent ATM DVR



Features

- > Tribrid: Support HDCVI/Analog/IP video input
- > Up to 8 cameras with SXGA(1280×1024) display
- > Face Recognition: Normal face recognition, abnormal face recognition and multi-face recognition
- > ATM Protection: Fake keyboard detection, fake card reader detection and misleading reminder detection
- > Scene Application: Tripwire detection, cross warning zone detection, abandoned/moved object detection, people loitering/gathering/queuing/running detection and etc.
- > Built-in kinds of ATM card number protocols, support bank card number and multi-information overlay.
- > H.264 dual-stream video compression
- > Full channel@720P realtime recording
- > HDMI/VGA/TV simultaneous video output
- > Up to 4 SATA HDDs, 1 eSATA, 3 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- > Built-in 7 inch screen

DH-HCVR0804AH-VD-I

Technical Specifications


Model		DH-HCVR0804AH-VD-I
System		
Main Processor		High performance embedded microprocessor
Operating System		Embedded LINUX
Video		
Input		8 channel
Standard	HDCVI	1080P/720P HDCVI Camera
	Analog	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
	IP	1080P/720P/D1/CIF IP Camera
Audio		
Input		8 channel, BNC
Output		1 channel, BNC
Bidirectional Talk		1 channel Input, BNC, 1 channel Output, BNC
Display		
Interface		1HDMI, 1 VGA, 1 TV, 1 LCD
Resolution		1280×1024, 1280×720, 1024×768, 800×600
Display Split		1/4/8/9
Privacy Masking		4 self-defined four-sided zones for privacy masking for each camera
OSD		ATM/POS information, camera title, time, video loss, camera lock, motion detection, recording
Recording		
Video/Audio Compression		H.264/G.711/PCM
Resolution		1080P(1920×1080)/720P(1280×720)/960H(960×576/960×480)/D1/4 CIF(704×576/704×480)/HD1(352×576/352×480)/2CIF(704×288/704×240)/CIF(352×288/352×240)/QCIF(176×144/176×120)
Record Rate	IP	Max 100Mbps
	HDCVI	8ch@720P
	Analog	All channel@960H(25/30fps)
Bit Rate		IP: 48~8192 Kb/s, Analog: 48~4096Kb/s
Record Mode		Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval		1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection & Alarm		
Trigger Events		Recording, PTZ, Tour, Alarm, Email, FTP, Buzzer & Screen tips
Video Detection		Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input		9 channel
Relay Output		5 channel
Playback & Backup		
Playback Channel		1/4

DH-HCVR0804AH-VD-I

Search Mode	ATM/POS, Time/Date, Alarm, Motion Detection & Exact search (accurate to second)
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom(any size)
Backup Mode	USB Device/Network /eSATA/Internal SATA burner
Network	
Ethernet	2RJ-45 port (10/100/1000M)
Network Functions	TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	4 SATA ports, up to 16TB
External HDD	1 eSATA port, up to 16TB
Auxiliary Interface	
USB	3 ports (2 rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	AC 100~240 V, 50/60 Hz
Power Consumption	25W(without HDD)
Working Environment	-10°C ~+55°C/10~90%RH/86~106kpa
Dimension(W×D×H)	200mm×300mm×182mm
Weight	3.5KG-4.5KG(without HDD)

DH-HCVR0804AH-VD-I

System Connection



Dahua Technology Co., Ltd.

1199' BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2015 Dahua Technology Co., Ltd.